

Issue date 14-Jan-2014

Revision Date 28-Apr-2016

Version 2

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Product name ThreeBond 1401

Recommended use of the chemical and restrictions on use

Recommended use Adhesive, Sealant

Details of the supplier of the safety data sheet

Manufacturer

ThreeBond Fine Chemical Co., Ltd.

Department in charge & Address

Production Engineering Division
1-1 Oyama-cho, Midori-ku
Sagamihara-shi, Kanagawa, Japan

Emergency telephone number

+81-42-774-1333

Section 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids	Category 2
Serious eye damage/eye irritation	Category 2
Reproductive Toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1
Category 1 Central nervous system retina systemic toxicity	
Category 3 Respiratory irritation, Narcotic effects.	
Specific target organ toxicity (repeated exposure)	Category 1
Category 1 Central nervous system, retina	

Label elements



Signal word

Danger

Hazard statements

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H360 - May damage fertility or the unborn child

H370 - Causes damage to organs

H372 - Causes damage to organs through prolonged or repeated exposure

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

Causes damage to the following organs: Central nervous system, retina, systemic toxicity.

Causes damage to the following organs through prolonged or repeated exposure: Central nervous system, retina.

Precautionary Statements - Prevention

- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. — No smoking
- Keep container tightly closed
- Use explosion-proof electrical/ventilating/lighting/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool

Precautionary Statements - Response

- IF EXPOSED: Call a POISON CENTER or doctor/physician
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- Call a POISON CENTER or doctor/physician if you feel unwell
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Rinse mouth.
- In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

- Store locked up
- Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

- Dispose of contents/container to an approved waste disposal plant

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Single substance or mixture

Mixture

Effective June 1, 2016, regarding Japan's Industrial Safety and Health Law's "Notifiable Dangerous and Harmful", target substances will be subjected to risk assessment in accordance with Japan's Industrial Safety and Health Law's "Harmful Substances Whose Names Are to be Indicated on the Label."

Chemical name	Weight-%	ENCS	ISHL No.	CAS No.
Methyl alcohol	65-75	(2)-201	-	67-56-1
Vinyl acetate	<1	(2)-728	-	108-05-4
Modified vinyl acetate	25-35	-	-	-

Industrial Safety and Health Law

Law Name	Chemical Name in Regulation	Ordinance Number
Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57, Para.1, Enforcement Order Art.18)	Methanol	36
Notifiable Substances (Law Art.57-2, Enforcement Order Art.18-2 Attached Table No.9)	Acetic acid, vinyl ester	180
Notifiable Substances (Law Art.57-2, Enforcement Order Art.18-2 Attached Table No.9)	Methanol	560

Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc

Law Name	Chemical Name in Regulation	Ordinance Number
Priority Assessment Chemical Substances (Law Article 2, Para.5)	Acetic acid, vinyl ester	28
Priority Assessment Chemical Substances (Law Article 2, Para.5)	Methanol	90

Section 4: FIRST AID MEASURES

INHALATION	Move victim to fresh air If breathing is irregular or stopped, administer artificial respiration Administer oxygen if breathing is difficult
Skin contact	Wash skin with soap and water
Eye contact	In case of contact with substance, immediately flush skin or eyes with running water for at least 20 minutes
INGESTION	Rinse mouth. Get medical attention.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Note to physicians	Effects of exposure (inhalation, ingestion or skin contact) to substance may be delayed. Keep victim warm and quiet.

Section 5: FIRE FIGHTING MEASURES

Flammable properties	Many liquids are lighter than water. HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames. Containers may explode when heated.
Suitable extinguishing media	Dry chemical, CO2, water spray or alcohol-resistant foam Move containers from fire area if you can do it without risk Dike fire control water for later disposal; do not scatter the material Use water spray or fog; do not use straight streams Water spray, fog or alcohol-resistant foam
Unsuitable extinguishing media	CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.
Specific hazards arising from the chemical	Vapors may form explosive mixtures with air Vapors may travel to source of ignition and flash back Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks) Vapor explosion hazard indoors, outdoors or in sewers Runoff to sewer may create fire or explosion hazard Those substances designated with a "P" may polymerize explosively when heated or involved in a fire
Special extinguishing media	Wear protection gear and extinguish from windward.
Special protective equipment for fire-fighters	No information available.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions	Full encapsulating, vapor protective clothing should be worn for spills and leaks with no fire ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) All equipment used when handling the product must be grounded Do not touch or walk through spilled material Stop leak if you can do it without risk
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas
Methods for containment	A vapor suppressing foam may be used to reduce vapors Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal
Methods for cleaning up	Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.
Prevention of secondary hazards	Keep ignition source away from spill.

Section 7: HANDLING AND STORAGE

Handling

Precautions for safe handling

Advice on safe handling Take equipment measures listed in Section 8. Wear protection gear.

Local and general ventilation Take equipment measures listed in Section 8. Wear protection gear.

Storage

Storage conditions Close lid. Avoid direct sun light and ignition source. Keep appropriate temperature. Refer to technical data sheet or material agreement and other documents for storage temperature range. Fire prohibited

Material of vessels and packaging Keep this product in original container. Do not put it back in the container.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure guidelines No data available as this product.

Chemical name	Japan	ISHL Working Environmental Evaluation Standards - Administrative Control Levels	ACGIH TLV
Methyl alcohol	TWA: 200 ppm TWA: 260 mg/m ³ Skin ISHL/ACL: 200 ppm	ISHL/ACL: 200 ppm	STEL: 250 ppm TWA: 200 ppm Skin
Vinyl acetate	-	-	STEL: 15 ppm TWA: 10 ppm

Engineering controls Install local ventilation or seal source of substances. Install safety shower, hand wash, and eye wash station. Clearly indicate the location.

Personal protective equipment

- Respiratory protection** In case of inadequate ventilation wear respiratory protection
- Hand protection** Wear appropriate protection glove (Made from non-permeable material such as polyethylene, rubber)
- Eye/face protection** Wear safety glasses with side shields (or goggles)
- Skin and body protection** Wear protection apron, protection boots. Wear long sleeve cloth.

Other information Wash hands thoroughly after handling. When using do not eat, drink or smoke.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid
Odor Alcohol odor
Color Transparent clear

<u>Property</u>	<u>Values</u>	<u>Remarks</u>
pH	No data available	
Melting point/freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	9 °C	Seta closed cup
Evaporation rate	No data available	
Flammability (solid, gas)		
Flammability limit in air		
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Specific gravity	0.88	
Water solubility	Partially miscible	

Autoignition temperature	No data available
Decomposition temperature	No data available
Dynamic viscosity	350 mPa·s

Section 10: STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Possibility of hazardous reactions	React with strong acid. Could cause fire.
Conditions to avoid	Heat
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	May generate harmful gas by incineration

Section 11: TOXICOLOGICAL INFORMATION

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Inhalation LC50 No data available as this product.

Numerical measures of toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl alcohol	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h = 64000 ppm (Rat) 4 h
Vinyl acetate	= 2900 mg/kg (Rat)	= 2335 mg/kg (Rabbit)	= 11400 mg/m ³ (Rat) 4 h = 11.4 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	No data available as this product.
Serious eye damage/eye irritation	No data available as this product.
Sensitization	No data available as this product.
Germ cell mutagenicity	No data available as this product.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical name	Japan	IARC
Vinyl acetate	2	Group 2B

*IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans*

Reproductive toxicity	No data available as this product.
STOT - single exposure	No data available as this product.
STOT - repeated exposure	No data available as this product.
Target organ effects	Central nervous system, Eyes, Gastrointestinal tract (GI), Respiratory system, Skin.
Aspiration hazard	No data available as this product.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity
Acute aquatic hazard No data available as this product.
Chronic aquatic hazard No data available as this product.

Chemical name	Algae/aquatic plants	Fish	Crustacea
Methyl alcohol	-	100: 96 h <i>Pimephales promelas</i> mg/L LC50 static 28200: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 19500 - 20700: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 18 - 20: 96 h <i>Oncorhynchus mykiss</i> mL/L LC50 static 13500 - 17600: 96 h <i>Lepomis macrochirus</i> mg/L LC50 flow-through	-
Vinyl acetate	-	14: 96 h <i>Pimephales promelas</i> mg/L LC50 static 15.04 - 21.54: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 26.1 - 36.63: 96 h <i>Poecilia reticulata</i> mg/L LC50 static	52: 24 h <i>Daphnia magna</i> mg/L EC50

Persistence and degradability No data available as this product.
Bioaccumulation No data available as this product.
Mobility in soil No data available as this product.

Endocrine disruptor information

Chemical name	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Endocrine disrupting potential
Vinyl acetate	Group III Chemical	-	-

Section 13: DISPOSAL CONSIDERATIONS

Waste from residues / unused products Dispose of in accordance with national, state and local regulations. Consult industrial waste management companies for waste. Do not release this product to natural environment nor reclaim.

Contaminated packaging Dispose containers as same as residual of this product.

Section 14: TRANSPORT INFORMATION

IMDG

UN/ID No. UN1992
Proper shipping name FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard class 3
Subsidiary hazard class 6.1
Packing group II
EmS-No F-E, S-D

ICAO/IATA (air)

UN/ID No.	UN1992
Proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard class	3
Subsidiary hazard class	6.1
Packing group	II

ADR

UN/ID No.	UN1992
Proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard class	3
Labels	6.1
Packing group	II
ERG code	3HP

Japanese regulations

UN Number	UN1992
Proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
Hazard class	3
Subsidiary hazard class	6.1
Packing group	II
Marine Transportation Safety Act	Flammable Liquids (Ministry of Transportation Ordinance Regarding Transport by Ship and Storage, Ordinance Art.3, Attached Table 1)
Civil Aeronautics Act	Flammable Liquids (MITL Notification for Air Transportation of Explosives etc., Ordinance Art.194, Attached Table 1)

Section 15: REGULATORY INFORMATION

Effective June 1, 2016, regarding Japan's Industrial Safety and Health Law's "Notifiable Dangerous and Harmful", target substances will be subjected to risk assessment in accordance with Japan's Industrial Safety and Health Law's "Harmful Substances Whose Names Are to be Indicated on the Label."

Fire protection law criteria Group 4 - Petroleums - 1st Class(not Water solubility)

Act on the Evaluation of Chemical Substances and Regulation of Their Manufacture, etc Priority Assessment Chemical Substances (Law Article 2, Para.5)

Industrial Safety and Health Law Harmful Substances Whose Names Are to be Indicated on the Label (Law Art.57, Para.1, Enforcement Order Art.18)
 Notifiable Substances (Law Art.57-2, Enforcement Order Art.18-2 Attached Table No.9)
 Class 2 Organic Solvents (Enforcement Order Attached Table No.6-2, Ordinance on Prevention of Organic Solvent Poisoning Art.1, Para.1, Item 5)

Section 16: OTHER INFORMATION

Issue date 14-Jan-2014

Other information Please contact to local sales offices for further information.

Disclaimer

Handle with care. The data in this document is not guaranteed. This information may be revised based on new findings or test results. This data sheet is authored in accordance with Japanese regulations.